

SentiO Lite



**16 Channel DVR with RS485;
Alarms;
PTZ control;
Remote Access – even from your mobile**

>> GUI OSD Interface.

- >> Supports 16CH CIF real-time recording.**
- >> Dual-stream design, the parameters for network monitoring and local recording can be set separately and have no impact on each other.**
- >> Support 16ch playback simultaneously.**
- >> Network function: IE Browser and CMS Software can monitor and manage multi- DVR (Max 255 DVR simultaneously).**
- >> Supports max 10 users simultaneously for remote view via IE browser.**
- >> Supports more than 18 kinds of protocol for PTZ control.**
- >> Supports pre-recording before alarm (about 10sec), will not lose any Suspicious video.**
- >> Supports two SATA HDD, each one max 2TB.**
- >> Support Mobile remote view via Symbian (S60V3,S60V5); WM (Windows Mobile);**
iOS(iPhone);Android;Blackberry(8520,8530,8900,9530,9550,9000,9700,9630).
- >> Supports VGA output, VGA and BNC can work simultaneously.**
- >> Supports sending alert event to the designated email while alarm triggered.**
- >> Multi-Language: Arabic/ Brazilian/ Bulgarian/ Chinese/ Czech/ English/ Finnish/ French/ German/ Greek/ Hungarian/ Portuguese/ Italian/ Japanese / Korean/ Polish/ Persian(Farsi)/ Portuguese/ Russian/ Romanian/ Spanish/ Swedish/ Thai/ Turkish/ Ukrainian/ Vietnamese, etc.**

Model	Senti○ Lite 16	
Video Compression Format	H264	
Video System	PAL / NTSC	
Video Input / Output	16 CH Input, 2 CH Output (BNC, VGA)	
Audio Input / Output	4 CH Input, 1 CH Output (RCA)	
Alarm Input / Output	4 CH Input, 1 CH Output	
Record	Resolution	NTSC: CIF (352 x 240) / 2CIF (704 x 240) / 4CIF (704 x 480)
		PAL: CIF (352 x 288) / 2CIF (704 x 288) / 4CIF (704 x 576)
	Frame Rate	NTSC:480fps-CIF
		PAL: 400fps-CIF
Image Quality Setting	Best, Better, Good, Medium, Normal and Low	
Hard Disk Storage	Max 2 x 2048GB SATA HDD	
Multiplex Operation	Live display, Record, Playback, Backup, Network Transmit, Mobile View	
Recording Mode	Manual, Timing, Motion Detection, Alarm	
Playback Mode	Slow Speed, Rapid Speed, Manual, Single-frame playing modes Supports positioning time by dragging the slider bar	
Backup Device	USB, USB Movable HDD, Network, USB DVD -RW	
Pre-alarm Recording	About 10 seconds before alarm	
Network Protocol	TCP/IP, PPOE, DNNS, FTP, NTP and UPNP	
Network Function	Supports max 10 users simultaneously for remote view via IE browser	
CMS software	YES	
Mobile View	YES	
Electronic zoom	YES	
Log record function	YES	
Image Tour	YES	
IR Remote control /USB Mouse	YES	
Video Loss Detection	YES	
Video Adjustable	Hue, Saturation, Contrast, Brightness	
Password Protection	YES	
Power-down recovery function	YES	
Power Source	DC 12V	
Size(mm)	248mm*330mm*64mm	
Weight with Packing	4kg	



Unit 39

Sir Frank Whittle Business Centre

Great Central Way

Rugby

Warwickshire

CV21 3XH

Tel :- 0844 800 1725

Fax :- 01788 544 549

www.plettac.co.uk